Mistakes You'll Want to Avoid When Laying Tile in Your

Mistakes You'll Want to Avoid When Laying Tile in Your Bathroombut there are some people who decide to actually install the tile on their own. If you happen to decide to put down the new tile for your bathroom remodeling project, then you'll have a bit job to do. When you get started, there are a few mistakes that you should definitely avoid, including the following ones.Preparing the Easy WayOne thing that you need to avoid is doing the preparation the easy way. When you go the easy route, it can make the whole job harder. Before you lay the tile, it is imperative that you make sure that the surface is both clean and smooth. You can use a sander to help get the surface smooth enough to work with. If you don't do this, it is going to be more difficult to install your tile.Not Getting Enough of the TileNot getting enough of the tile you have chosen is another mistake you really need to avoid. You see, you never know when you may need a bit more tile. Your measurements could have been off, you may make a mistake or even crack a tile, then you'll need a new one. So, it's a good rule of thumb to get about 15% more than you plan on needed, just in case there is a problem. Then, if you do have a bit left over, you can keep it in case there is a tile that gets cracked or damaged at a later date.Not Using a Waterproof AdhesiveNot using waterproof adhesive is another big mistake to avoid. Since you are laying tile in the bathroom, where there is a lot of water and moisture, you need to make sure that you use an adhesive that is waterproof. If you don't use a waterproof adhesive, it can later crumble or rot away and cause problems with your tile. So, make sure that you go with the right adhesive for the tile in the bathroom.Uneven Spacing of the TilesYou'll also want to avoid the mistake of getting uneven spacing between the tiles you are installing. If the spacing is off, in the future your tiles may come loose. So, it is best to measure the gaps that are between the tiles, so you know that they are spaced correctly and you don't have problems in the future that could have been prevented.Grouting Before the Tile is ReadyGrouting the tile before it is read is another problem to avoid. Many people try to grout right away, but you should really wait a whole 24 hours before you decide to do the https://zipleaf.us/Companies/Sacramento-HVAC-Contractor-7 grout work. This way you'll be sure that the adhesive on the tile has really set and they won't move around while you are adding the grout to the tiling.